


Specifications

▶ Metal Options

Several metal choices and color choices are available:

1. Stainless Steel: Grade CS304 with #4 Satin Polish, 0.030"tk, meets ASTM A240
2. Brushed Aluminum: Grade AA3003H14, 0.040"tk, meets ASTM B209 | AMS-QQ-A-250/2
3. Aluminum Diamond Plate: Grade AA3003H22, 0.045"tk, meets ASTM B632
4. Anodized Aluminum Diamond Plate: Grade AA3003H22, 0.045"tk, meets ASTM B632 | ASTM B-137 | MIL-A-8325F | ASTM B136 | ASTM B580 Type C
5. Galvanized Steel: Grade CSB-G90, 0.030"tk, meets ASTM A653
6. Aluminum Painted: AA3105H14, 0.040"tk, Paint Pencil Hardness meets F-2H
7. Steel Painted: GR-50 Class 2, Solar Reflectant Fluropon-Kynar[®] Paint, Paint Pencil Hardness meets HB-F

▶ Size Options



Product Family	
Heights (A)	Lengths
2", 4-3/4", 6"	48" and 96"
Above are standard sizes. Custom Sizes available upon request	

▶ Inside and Outside Corner Options

2 types of corner methods are available:

1. For DIY consumer grade installations, our Pre-Formed Inside Corner and Pre-Formed Outside Corner may be used.
2. For commercial grade installation, miter cutting pieces in the field is recommended for best fit and least number of seams.



Base Molding MX[™]
Pre-Formed Inside Corner
P/N: HBMIC



Base Molding MX[™]
Pre-Formed Outside Corner
P/N: HBMOG

▶ Attachment Method Options

2 types of attachment methods are available:

1. For DIY consumer grade installations, our Self-Adhering feature may be used.
2. For commercial grade installation, we suggest using a construction grade adhesive rather than our Self-Adhering feature. Our Self-Adhering feature is great for DIY residential use due to its simplicity, however for commercial grade installations, contractors generally prefer to use a construction grade adhesive rather than our Self-Adhering feature for two reasons: (1) a construction grade adhesive allows a working time so that the position of the piece can be fine tuned – on the other hand our Self-Adhering feature bonds the piece instantaneously with no working time. (2) a construction grade adhesive allows the piece to sit flush on the wall – however our Self-Adhering feature has a finite thickness of appx 1/32" to 1/16" which keeps the piece off the wall a bit. Use a construction adhesive formulated for the wall type to be installed onto. For installation onto dry wall, we offer Liquid Nails[®] Polyurethane formulation.



high flow bonding adhesive

For more information, contact:

Kim Wilson

T. 1-866-556-6324
F. 1-361-906-0824
E. kwilson@elite-xpressions.com
Store. elite-xpressions.com